



## Bypass-Less Slide-In System

White Magic's exclusively engineered **HEATSMART™** Technology



- KOHLER AEGIS® 24 Hp Engine
- ROOTS™ 45 Blower
- CAT PUMP® 5CP Pump
- 230°+ Working Water Temp.
- 120 gal. Recovery Tank (standard)
- Automatic Heat Diverters (2)
- **HEATSMART™** Technology
- Pump Disengagement Clutch
- Last Stage Chemical Injection
- Progressive Silencing System
- Pulsation Dampener
- 150 ft. Vacuum Hose
- 150 ft. Solution Hose
- 5 Gallon Chemical Jug w/ SS Holder
- 12" 2 Jet Scrub Wand
- Platinum Warranty

"The Clear Choice"  
**White  
Magic**  
INC.

**White Magic Inc.**

**(800) 422-1128**

[www.whitemagicinc.com](http://www.whitemagicinc.com)

**White  
Magic**  
INC.  
"GET MORE WITH LESS"

"OUR FUTURE DEPENDS ON YOUR COMPLETE SATISFACTION"

White Magic Inc. 11 Main Street, Salisbury, MA 01952 - TEL# (800) 422-1128 - FAX# (978) 462-9170 - WEB: [www.whitemagicinc.com](http://www.whitemagicinc.com)



## SPECIFICATIONS

### Engine:

KOHLER AEGIS® 24 Hp  
Liquid Cooled  
Electric Start  
Oil Sentry Shut-down  
Engine Exhaust Diverter  
Coolant Temp. Shut Down

### Blower

ROOTS™ 45  
345 cfm @ 14 in. Hg. max.  
Blower Exhaust Diverter

### Pump

CAT PUMP® 5 CP Pump  
5 gpm  
2000 PSI  
Pump Disengagement Clutch  
Pulsation Dampener

### Recovery Tank

120 gallons (standard)  
2" Drain  
Automatic High-level Shut-off

### Optional Equipment

70 Gallon Fresh Water Tank  
External Automatic Pump-Out  
Inline Filter Recovery System  
Hose Reels  
(More Optional Equipment Available)

### Heat Exchangers

230°+ Water Temps.  
Exclusively Engineered High  
Efficiency Finned Tube Coil

### HEATSMART™ Technology

Bypass-less  
No Filters  
No Solenoids  
No Thermo Relief Valves  
Automatic Heat Diverters (2)

### Size (Footprint):

27" W x 41" L x 31"  
900 lbs.  
(Approx. Total System Weight With No Water)

**White Magic Inc.**

**(800) 422-1128**

[www.whitemagicinc.com](http://www.whitemagicinc.com)



White Magic Inc. © JULY 2007  
COMMANDER L Cutsheet v 1.0

\*All features are subject to change without notice. All specifications are subject to change without notice. Major components specifications are manufacturers maximum ratings. System is de-rated for maximum component life. Engine and blower are used to 70-80% capacities. System pressure is set at 1200 PSI.

**"OUR FUTURE DEPENDS ON YOUR COMPLETE SATISFACTION"**

White Magic Inc. 11 Main Street, Salisbury, MA 01952 n TEL# (800) 422-1128 n FAX# (978) 462-9170 n WEB: [www.whitemagicinc.com](http://www.whitemagicinc.com)