



PRO-2000



INC. The Industry's ONLY TRUE DUAL WAND Unit!

Direct Drive Carpet Cleaning System

29 Years of Consistent Quality & PERFORMANCE!

White Magic's **Direct Drive System** is the industry's only true dual wand unit. Powered by (2) independent **ROOTS™ 45 Blowers**, dual independent **100 gallon recovery tanks** and **dual heat exchangers**. The **PRO-2000** is ideal for commercial and flood damage operations. If desired, the **PRO-2000** can easily be configured to supply the power of both blowers to just a single wand, providing exceptional air-flow over long distances. The units compact design allows the **PRO-2000** to be easily installed into a standard size van, allowing ample room for tools and accessories.

Twin ROOTS™ 45 Blowers



NEED TRUE DUAL WAND PERFORMANCE ??? The Answer . . .

INDEPENDENT BLOWERS

Direct Drive Carpet & Upholstery Cleaning System

FEATURING:

- Front End Installation Kit
 - Now Available w/ 3 Speed Electronic Throttle Control For Many GM & Ford Vans
- 1-1/8" TGP Steel Drive Shaft
- (2) **ROOTS™ 45 Blowers** (Independent)
- (2) Stainless Steel Heat Exchangers
- (2) 100 Gallon Recovery Tanks (Independent)
- Fresh Water Tank -125 Gallon
- **CAT PUMP® 5CP Pump**
- Pump Disengagement for Water Extraction
- Stainless Steel Chemical Pump
- Tool-less Console Cover
- Platinum Guarantee Warranty



"OUR FUTURE DEPENDS ON YOUR COMPLETE SATISFACTION"

White Magic Inc. 11 Main Street, Salisbury, MA 01952 ■ TEL# (800) 422-1128 ■ FAX# (978) 462-9170 ■ WEB: www.whitemagicinc.com

PRO-1000_1200 CUTSHEET Q-P1 ,v1.0



PRO-2000



Twin **ROOTS™** 45 Blowers



**INDEPENDENT
BLOWERS**

The Industry's **ONLY TRUE DUAL WAND Unit!**

Direct Drive Carpet Cleaning System

SPECIFICATIONS:

Blowers (Independent)

- (2) **ROOTS™** 45 Blowers - 340 CFM each
- 14" Hg. Lift
- Belt Drive
- Oil Level Sight Tube
- Oil Drain System

Pump

- CAT PUMP®** 5CP Pump
- 5 GPM
- 2000 PSI (Max Pump Rating)
- Pump Disengagement Clutch

Recovery Tanks

- (2) **100 Gallon Tanks** - (Independent)
- 2" Drain Assembly
- Automatic High Level Shut-off
- Marine Grade Aluminum Construction

Heat Exchange System

- (2) **Stainless Steel Heat Exchangers**
 - 200 Ft. Copper Coil (per heat exchanger)
 - Reverse Flow
- Water Temp 185°-200°F

Chemical Injection System

- Last Step Chemical Injection
- GPH Metering Valve
- Stainless Steel Chemical Pump
- Vacuum Assisted Priming Valve

Weight & Dimensions

- 26"W x 46"L x 32"H
- 1170 Lbs. (PRO-2000 Unit Weight)

Standard Equipment

- Main Frame Assembly
- 125 Gallon Fresh Water Supply Tank
- (2) 100 Gallon Recovery Tanks
- 150 ft. Vacuum Hose
- 150 ft. Solution Hose
- 12 ft. Lead Hose
- 6 Gallon S.S. Chemical Rack
- (2) 5 Gallon Chemical Jugs w/ Double S.S. Tray
- 2 Jet Scrub Wand
- 3" S.S. Pad Holder
- Operation Manual
- Platinum Guarantee Warranty



**29 Years of
Consistent Quality
&
PERFORMANCE!**

NEED TRUE DUAL WAND PERFORMANCE ??? The Answer . . . PRO-2000

PRO-2000 CUTSHEET Q-P1 White Magic Inc. © OCT 2004

*All features are subject to change without notice. All specifications are subject to change without notice. Major components specifications are manufacturers maximum ratings. System is de-rated for maximum component life. Blowers are used to 70-80% capacities. System pressure is set at 1200 PSI.

"OUR FUTURE DEPENDS ON YOUR COMPLETE SATISFACTION"

White Magic Inc. 11 Main Street, Salisbury, MA 01952 ■ TEL# (800) 422-1128 ■ FAX# (978) 462-9170 ■ WEB: www.whitemagicinc.com